

N251DA XL

Automatsko spužanje testere

Model	Šifra artikla
N251DA XL	8.48.80.50

**TROFAZNI
MOTOR**

TEHNIČKE KARAKTERISTIKE

- Snažan trofazni indukcion motor sa dve brzine, sa reduktorom motora podmazanim uljem.
- Ruka testere, stega i fleksibilni mehanizam koji su izrađeni od livenog gvožđa.
- Čelična klizna vodica lista testere sa ležajevima.
- Stega sa sistemom brzog stezanja.
- Prednja poluga za otpuštanje zakretnog mehanizma, integrisana u samo postolje.
- Pumpa za podmazivanje sa aluminijumskim kućištem.
- Veliki točkić za jednostavno zatezanje lista testere.
- Manometar za kontrolu zategnutosti lista testere (600 – 1000 kg/cm²).

STANDARDNA OPREMA

- Postolje u kompletu za montažu.
- Rezervoar za ulje za podmazivanje
- Pumpa za podmazivanje.
- Graničnik za šipke za serijsko sečenje.
- Ključevi za podešavanje, zamenu lista testere i demontažu zaštite lista.
- Četka za čišćenje lista testere.
- Hidraulični cilindar sa regulacijom brzine spuštanja konzole.



KAPACITET REZANJA

			
0°	L 240 x H 160 mm L 250 x H 110 mm	225 mm	185x185 mm
45°	L 135 x H 185 mm L 145 x H 150 mm	150 mm	145x145 mm
60°	L 63 x H 107 L 69 x H 90	70 mm	70x70 mm



- Snažan trofazni indukcion motor sa dve brzine



- Hidraulični cilindar sa regulacijom protoka



KILOWATT

0,75/1,1³


2480x27x0,9



6/10*




45/90



WATT

100


a x b x h
mm

1385x580x890



kg

200

*Standardni bimetalni list testere sa dodatkom kobalta
3~ 400 Volt – Hz 50 trofazni motor


femi