

N257 DA DG

Automatsko spuštanje testerne glave

NEW

Tračna testera 2500 – industrijska serija

Model	Šifra artikla
N257DA DG	8.48.80.56

Klizna stega 0°–60°
ulevo i 0°–45° udesno

TEHNIČKE KARAKTERISTIKE

- Snažan trofazni indukcionni motor sa dve brzine, sa reduktorom podmazanim uljem.
- Ruka testere, stega i zakretni mehanizam izrađeni od livenog gvožđa.
- Čelična klizna vodica lista testere sa ležajevima.
- Stega sa sistemom brzog stezanja.
- Pumpa za podmazivanje sa aluminijumskim kućištem.
- Veliki točkić za jednostavno zatezanje lista testere.
- Manometar za kontrolu zategnutosti lista testere
- (600 – 1000 kg/cm³).

STANDARDNA OPREMA

- Postolje u kompletu za montažu.
- Rezervoar za ulje za podmazivanje.
- Pumpa za podmazivanje.
- Graničnik za šipke za serijsko sečenje.
- Ključevi za podešavanje, zamenu lista testere i demontažu zaštite lista.
- Četka za čišćenje lista testere.
- Hidraulični cilindar sa regulacijom brzine spuštanja konzole.



TROFAZNI
MOTOR

MAX
253 mm

KAPACITET REZANJA

			
0°	245xH148- 253xH70	225 mm	180
45° ulevo	90xH180	140 mm	120
60° udesno	85xH115	90 mm	90
45° udesno	132xH180	148 mm	140



• Hidraulični cilindar sa regulacijom protoka



KILOWATT

0,75/1,1[3~]



2480x27x0,9



6/10*



45/90



WATT

100



a x b x h
mm

1385x580x890



Kg

235

*Standardni bimetalni list testere sa dodatkom kobalta
3~ 400 Volt – Hz 50 trofazni motor



femi