

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

C200 TSS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Fuel gas

Uses advised against

Consumer use

1.3 Details of the supplier of the safety data sheet

Address

ROTHENBERGER Werkzeuge GmbH

Industriestraße 7

65779 Kelkheim

Telephone no. +49 (0) 61 95 / 800 - 1

Fax no. +49 (0) 6195 / 800 - 3500

e-mail info@rothenberger.com

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Flam. Gas 1; H220

Press. Gas; H280

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02

Signal word

Danger

Hazard statement(s)

H220

Extremely flammable gas.

H280

Contains gas under pressure; may explode if heated.

Precautionary statement(s)

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	In case of leakage, eliminate all ignition sources.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P251	Do not pierce or burn, even after use.

Labelling information

It is allowed to use the reduced labelling for gas containers for propane, butane or liquefied petroleum gas (LPG) based on Annex I, point 1.3.2 (EC Regulation 1272/2008 Annex I, 1.3.4).

2.3 Other hazards

Contact with the liquid can cause cold burns or frostbite. During and after use possible formation of combustible mixture with solvents.

PBT assessment

The product is not considered to be a PBT.

vPvB assessment

The product is not considered to be a vPvB.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Hydrocarbons, C3-4-rich, petroleum distillates	pls. refer to footnote (1)	
	68512-91-4 270-990-9 649-083-00-0 -	Flam. Gas 1; H220 Press. Gas; H280	< 100.00 Vol%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove affected person from danger area, lay him down. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of persisting adverse effects, consult a physician.

After inhalation

Ensure supply of fresh air.

After skin contact

In case of frostbite, rinse with plenty of water. Do not remove clothing.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Call a doctor immediately.

After ingestion

Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed**Symptoms**

Frostbite; Dizziness; Shortness of breath; Unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon monoxide and carbon dioxide; Nitrogen oxides (NO_x); May explode if exposed to heat. Liquefied gas: Spilled liquid can cause cold burns. This gas is heavier than air and may accumulate in low areas.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Containers close to fire should be transferred to a safe place. Cool closed containers exposed to fire with water. Pressure increase, bursting and explosion hazard during heating.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation. Keep away sources of ignition. Evacuate all unprotected personnel from the danger zone. Use personal protective clothing.

For emergency responders

Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Avoid release in the environment.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Room ventilation via exhaust system.

6.4 Reference to other sections

Information regarding safe handling, see chapter 7. Information regarding personal protective measures, see chapter 8. Information regarding waste disposal, see chapter 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far as possible by the state of the art. Provide good room ventilation even at ground level (vapours are heavier than air). Open and handle container with care. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Handle with care - avoid bumps, friction and impact.

General protective and hygiene measures

Wash hands before breaks and after work. Do not inhale gases. Do not eat, drink or smoke during work time. Keep away from food, drink and animal feeding stuffs. Avoid contact with eyes and skin. Remove contaminated clothing and shoes and launder thoroughly before reusing.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Isolate from sources of heat, sparks and open flame. Take precautionary measures against electrostatic loading (earthing necessary during loading operations). Use explosion-proof equipment/fittings and non-sparking tools. Electrical equipment should be protected to the appropriate standard.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

Keep container tightly closed in a cool, well-ventilated place, open and handle carefully. Protect from heat and direct sunlight.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Incompatible products

Do not store together with: oxidizing agents; oxidizing substances

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
List of approved workplace exposure limits (WELs) / EH40			
Butane			
	WEL short-term (15 min reference period)	1810 mg/m ³	750 ppm
	WEL long-term (8-hr TWA reference period)	1450 mg/m ³	600 ppm
	Comments	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	

8.2 Exposure controls**Appropriate engineering controls**

Ensure adequate ventilation, local exhaust at the work station if necessary.

Personal protective equipment**Respiratory protection**

Self-contained breathing apparatus. In case of insufficient ventilation or long-term effect use breathing apparatus.

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

insulated gloves; Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Chemical-resistant work clothes. Fire-resistant antistatic protective clothing. Protective shoes.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form/Colour
Compressed liquified gas
colourless
Odour
characteristic
Odour threshold
No data available

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

pH value	
No data available	
Boiling point / boiling range	
No data available	
Melting point / melting range	
No data available	
Decomposition point / decomposition range	
No data available	
Flash point	
Value	< -50 °C
Auto-ignition temperature	
Value	> 400 °C
Source	supplier
Oxidising properties	
No data available	
Explosive properties	
This product is not explosive. In and after use danger of production of inflammable compounds.	
Flammability (solid, gas)	
No data available	
Lower flammability or explosive limits	
Value	1.5 % vol
Source	supplier
Upper flammability or explosive limits	
Value	8.8 % vol
Source	supplier
Vapour pressure	
No data available	
Vapour density	
No data available	
Evaporation rate	
No data available	
Relative density	
No data available	
Density	
No data available	
Solubility in water	
Source	supplier
Comments	Not miscible or difficult to mix
Solubility(ies)	
No data available	
Partition coefficient: n-octanol/water	
No data available	
Viscosity	
No data available	

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

Trade name: C200 TSS**Product no.:** 035901-A, 035901-B**Current version :** 1.0.0, issued: 02.07.2019**Replaced version:** -, issued: -**Region:** GB**10.1 Reactivity**

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Risk of formation of explosive gas mixtures in air. Reactions with oxygen. Exothermal reactions are possible in the event of contact with incompatible substances.

10.4 Conditions to avoid

Temperatures > 50°C. Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Oxidizing agents; Reactions with oxidizing substances

10.6 Hazardous decomposition products

None, if handled according to intended use.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute oral toxicity**

No data available

Acute dermal toxicity

No data available

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard

No data available

SECTION 12: Ecological information**12.1 Toxicity****Toxicity to fish (acute)**

No data available

Toxicity to fish (chronic)

No data available

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment**Results of PBT and vPvB assessment**

PBT assessment

The product is not considered to be a PBT.

vPvB assessment

The product is not considered to be a vPvB.

12.6 Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

dispose of in accordance with local regulation.

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Compressed gas packaging under pressure. Do not open by force. Do not heat above 50°C. Dispose of compressed gas packagings only if completely discharged. Do not burn empty compressed gas packagings. Do not pierce, cut or weld uncleaned containers.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class

2

Classification code

5F

UN number

UN2037

Proper shipping name

RECEPTACLES, SMALL, CONTAINING GAS

Tunnel restriction code

D

Label

2.1

14.2 Transport IMDG

Class

2

UN number

UN2037

Proper shipping name

RECEPTACLES, SMALL, CONTAINING GAS

EmS

F-D, S-U

Label

2.1

14.3 Transport ICAO-TI / IATA

Class

2.1

UN number

UN2037

Proper shipping name

Receptacles, small, containing gas

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

Label 2.1

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 40
---	-------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P2
--	----

Other regulations

Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A chemical safety assessment has been carried out for this substance.

SECTION 16: Other information**Further information**

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Sources of key data used to compile the data sheet:

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

National Threshold Limit Values of the corresponding countries as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Department issuing safety data sheet

UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Trade name: C200 TSS

Product no.: 035901-A, 035901-B

Current version : 1.0.0, issued: 02.07.2019

Replaced version: -, issued: -

Region: GB

Document protected by copyright. Alterations or reproductions require the express written permission of UMCÖ GmbH.
Prod-ID 753548